


Discover the power of **Aerogel** Insulation



KROSSLINKER

Product Name	External dimensions L x W x H	Aerogel insulation wall thickness	Payload capacity	Tare weight	Temperature Range	Minimum performance**
	[cm]	[cm]	[L]	[kg]		[h]
Cryar 1L mini*	23 x 23 x 25	2.5	1	3.3	+2°C to +8°C	≥40
Cryar 2L express*	26 x 26 x 28	2.5	2	4.8	+2°C to +8°C	≥48
Cryar 2L light express	23 x 23 x 25	2.5	2	3.4	+2°C to +8°C	≥36
Cryar 2L extended	24.5 x 24.5 x 26.5	2.5	2	4.2	+2°C to +8°C	≥58
Cryar 2L dry ice	26 x 26 x 28	2.5	2	4.8	-80 °C to -40 °C	≥48
Cryar 4kg mobile box*	26 x 26 x 24	2	3.7	2.9	+2°C to +8°C	≥20
Cryar 4L express*	26 x 26 x 28	2	4	4.3	+2°C to +8°C	≥36
Cryar 6L MAX durable	33 x 33 x 35	3	6	8.6	+2°C to +8°C	72-96
Cryar 8L MAX durable	32 x 32 x 34	3	8	7.5	+2°C to +8°C	≥48
Cryar 8L MAX durable extended	35 x 35 x 37	4.5	8	8.8	+2°C to +8°C	≥72
Cryar 13L MAX durable	38.5 x 38.5 x 39.5	3.5	13	13	+2°C to +8°C	72-96
Cryar 14L mobile box*	34 x 34 x 36	1.5	14	5.7	+2°C to +8°C	≥20
Cryar 25L MAX durable	48 x 48 x 49	4.5	25	25	+2°C to +8°C	96-120
Cryar pallet shippers			Coming soon			

**No-spill solution – gel PCM-based cooling medium*

***Minimum performance is qualified based on ISTA 7D summer*

ISTA 7D Summer Profile

